

# S5 SERIES

## 700VA to 5KVA

The S5 Series is a true online double conversion UPS designed to deliver clean computer grade power with a pure sinewave output.

The unit incorporates Insulated Gate Bipolar Transistor (IGBT) High Frequency, Pulse Width Modulated (PWM) microprocessor controlled technology.

The S5 units are available in standalone and in 19" Rackmount design. RS232 communication port comes as standard.

SNMP modules are available as an option allowing integration of the UPS within a network management environment.

### MONITORING AND AUTO SHUTDOWN SOFTWARE:

- UPSMON is the monitoring software that allows you to:
- Supervise mains voltage, output voltage, load, battery charge status and other important parameters
- Automatic shutdown of the system
- Programme weekly UPS on/off times
- Personalise UPS parameters

#### **BATTERY EXPANSION**

The standard autonomy UPS unit houses its batteries within the UPS enclosure. Increased battery autonomy options can be catered for with the addition of matching battery cabinet(s) as required.

One unique feature of this product which tends to be overlooked by other manufacturers, is the recharge time i.e. to charge the batteries from a discharged state to a 100%.

Typically a UPS unit with 8 hours autonomy would take up to 2 days to recharge. With the EPI UPS it would take between 8 to 10 hours to recharge. We achieve this by including additional battery chargers in parallel to allow faster battery charging.



### MAIN FEATURES:

- Wide input voltage window
- Small footprint
- Load bar graph on display
- Battery capacity on display
- Replace battery warning signal
- High efficiency
- No break bypass
- Programmable on/off switch facility
- Extended autonomy options
- Also deliverable in 19" Rackmount version



# TECHNICAL DETAILS

S5 Series	700	1000	1500	2000	3000	4000	5000	
Input								
Nominal Voltage		220V-230V-240V						
Accepted Voltage		170-276 Vac						
Input Frequency		50/60 Hz Autorange ± 5Hz						
Input Power Factor	>0.93	>0.93	>0.99	>0.99	>0.99	>0.99	>0.99	
Output								
Nominal Power	700 VA	1000 VA	1500 VA	2000 VA	3000 VA	4000 VA	5000 VA	
Voltage	230V	230V	230V (selectable 220/240)	230V (selectable 220/240)	230V (selectable 220/240)	230V (selectable 220/240)	230V (selectable 220/240)	
Waveform		Pure Sine Wave						
Voltage Tolerance		±1.5%						
Voltage Distortion		<2%						
Frequency		50 or 60 Hz Selectable						
Frequency Tolerance		± 0.5%						
Crest Factor		3:1 (till 100% of the load)						
Overload		150% In per 2 sec						
Sockets		4 x iec320 or 4 x UK 13A - Terminals						
System								
Efficiency AC-AC	90%	90%	89%	90%	90%	90%	90%	
Batteries	2/12V/7Ah	3/12V/7Ah	5/12V/7Ah	6/12V/7Ah	10/12V/7Ah	10/12V/7Ah	15/12V/7Ah	
Transfer Time		0 ms (no breaks)						
Communication Port		RS232						
Protections		Excessive Battery Discharge ·Over Current · Short Circuit · Over Voltage · Under Voltage · Temperature						
Noise Level		<40 dbA at 1m						
Standards		Safety EN 50091-1-1 EN 50091-2/EN60950 Electromagnetic Compatibility EN55022/B, EN55082 (IEC801-2,3,4,5)						
Physical								
Autonomy Minutes	6	8	10	8	10	8	8	
Dimensions W x D x H (mm)	158x376x231	158x376x231	158x485x340	158x485x340	158x590x480	158x590x480	230x650x530	
Weight (kg)	7	10	23	27	43	44	65	

 $<sup>{}^{\</sup>star}$ Extended autonomies available

Head Office UK:

EPI Service Limited · Witan Park, Avenue Two, Station Lane, Witney, Oxfordshire OX28 4FH

 $\label{eq:complex} \textbf{Telephone} \quad \textbf{+44 (0) 1993 708855} \cdot \textbf{Facsimile +44 (0) 1993 708850} \cdot \textbf{e-mail: sales@epi-uk.com} \cdot \textbf{web www.epi-uk.com} \\$ 

France:

EPI France S.A.R.L. · 30, Avenue de l'Amiral Lemonnier, 78160 Marly-le-Roi, France.

Telephone +33 (0)1 39 17 15 57 · Facsimile +33 (0)1 39 17 15 58 · e-mail: sales@epi-fr.com · web www.epi-fr.com

Singapore

Excellence in Power Integration (S) Pte Ltd  $\cdot$  18 Mohamed Sultan Road, #03-03, Singapore 238967.

 $\label{eq:total_com} \textbf{Telephone} \quad \textbf{+65.733.5900} \cdot \textbf{Facsimile +65.735.6400} \cdot \textbf{e-mail: sales@epi-ap.com} \cdot \textbf{web www.epi-ap.com}$ 

Local Partners in:

 $AUSTRALIA \cdot AUSTRIA \cdot CHINA \cdot CZECH \ REPUBLIC \cdot DENMARK \cdot FINLAND \cdot GERMANY \cdot GREECE \cdot HONG \ KONG \cdot HUNGARY \cdot INDONESIA \cdot INDIA \cdot ITALY \cdot JAPAN \cdot MALAYSIA \cdot THE \ NETHERLANDS \cdot NORWAY \cdot PAKISTAN \cdot PHILIPPINES \cdot POLAND \cdot PORTUGAL \cdot RUSSIA \cdot SAUDI \ ARABIA \cdot SPAIN \cdot SWEDEN \cdot TAIWAN \cdot THAILAND$ © 2002, EPI Service Limited reserve the right to change any or all of the specifications indicated or implied without prior notice.